


AVAILABLE CONFIGURATION : VERTICAL OR HORIZONTAL

ASME | CSA | CRN

Overview

Designed for commercial and industrial applications, the RCG model provides a reliable solution compliant with ASME and CSA standards, with customization options tailored to project requirements.




PRESSURE	125 à 200 psi
DIAMETER	24" à 144"
CONFIGURATION	Vertical / Horizontal
MATERIALS	Carbon Steel / Stainless

Operating Pressure

psi	kPa
125	862
150	1 034
200	1 379

Key Features

- Designed in accordance with ASME Section VIII, Division 1
- CSA B51 compliant
- CRN registered in all provinces
- Hydrostatically tested
- Replaceable aluminum anodes



Options

- Horizontal version with steel saddle supports

Insulation

- Fiberglass insulation with FSK vapor barrier facing
- Stucco aluminum cladding
- Thermal performance: R-4 per inch

Connections & Inspection Access

- Connections: Victaulic, Flanged, Threaded
- Inspection Access: Handhole (4" x 6", 6" x 8") / Manway (12" x 16")



For a custom design tailored to your project, contact your local representative or email us at info@gestionslbkg.com

Warranty

Standard
1 Year

With Concrete Lining
10 Years (Internal Inspection Required Every 24 Months)



CRN